



# Valspar® Medallion® Plus Exterior Latex Semi-Gloss Paint

---

## Series 2600

### GENERAL DESCRIPTION

Valspar® Medallion® Plus Exterior Paint & Primer is a 100% acrylic formula that helps prevent cracking and peeling through weather changes. Rain Ready in two hours, this mildew-resistant coating offers great hide & coverage. Valspar® Medallion® Plus Exterior can be applied to a variety of properly prepared exterior wood and metal siding and trim.

#### **Product Features:**

- Rain Ready – dries in two hours
- High-hiding
- Great durability
- Resists cracking & peeling
- 100% acrylic
- Provides a mildew-resistant finish
- Easy cleanup

### WHERE TO USE

Properly prepared exterior surfaces of wood, hardboard, aluminum siding, vinyl siding, masonry, brick, stucco, cement composition panels and metal. Not for use on floors.

### SHIPPING AND PACKAGING

#### **Freight Classification:**

Paint or paint related material. Protect from freezing.

#### **Packaging:**

- Quart – 4 per carton
- Gallon – 4 per carton
- 5 gallon pail

### COMPOSITION

#### **Base and Fill Levels**

(oz./gal.)

<b>White</b>	128
<b>Pastel</b>	126
<b>Tint Base</b>	124
<b>Clear Base</b>	116

### APPLICATION

Stir paint thoroughly. Intermix containers for uniformity. When air temperature is 40°F, substrates may be colder; prior to painting, check to be sure the air, surface and material temperatures are above 40°F and at least 5°F above the dew point. Avoid using if rain or snow is expected within 2 hours. Do not apply when air or surface temperatures may drop below 40°F within 48 hours. On large expanses of metal siding, the air, surface and material temperatures must be 50°F or higher. No reduction necessary. Some deep or bright colors, surface conditions and application techniques may impact coverage and require multiple coats to achieve your optimal coverage. For additional application tips go to Valspar.com.

#### **Airless Spray:**

**Pressure:** 2000 PSI

**Tip:** 0.015–0.019"

**Brush:** Premium-quality polyester

**Roller:** Premium-quality roller 3/8" nap

### CLEANUP/STORAGE/ DISPOSAL

Clean up with warm, soapy water. Do not pour unused contents down the drain. Consult with local authorities for proper method of disposal and recycling.

### PRODUCT SPECIFICATIONS

- o **Vehicle Type:** Acrylic resin
- o **Viscosity:** 94–100 Krebs Units
- o **Sheen:** 35–45 Units @ 60° angle
- o **Flashpoint:** 205 °F
- o **VOC:** < 50 g/L – 0.42 lb/gal as per 40 CFR 59.406
- o **Volume Solids:** 33%
- o **Weight Solids:** 43%
- o **Weight Per Gallon:** 9.93 lbs./gal.
- o **Practical Coverage:** Covers approximately 300–400 sq. ft. per gallon (27–37 m<sup>2</sup> per 3.78 L) depending on surface porosity. Do not thin.
- o **Recommended Film Thickness:** 4.0 mil Wet 1.5 mil Dry
- o **Dry Time @ 77 °F and 50% Relative Humidity**
  - ▯ **To The Touch:** 1 hour
  - ▯ **Recoat:** 4 hours
- o **Application Temperature:** 40–90 °F (5–32 °C)
- o **Storage Temperature:** 40–90 °F (5–32 °C)



# Valspar® Medallion® Plus Exterior Latex Semi-Gloss Paint

---

## Series 2600

### **SURFACE PREPARATION**

Remove surface contaminants with an appropriate cleaner, rinse thoroughly and allow to dry. Remove peeled or damaged paint. Sand glossy surfaces dull. Seal stains with the appropriate primer. Caulk around windows, doors and other openings after spot priming bare surfaces. Knots and some woods, such as redwood and cedar, contain a high amount of tannin, a colored wood extract. If applied to these unpainted woods, the first coat of paint may show some staining, but it will be trapped in the first coat. A second coat will uniform the appearance. If staining persists, spot prime severe areas with a stain-blocking primer. Previously Painted: Spot prime bare areas, allow to dry and paint entire surface. Unpainted: Prime the surface with this product before applying the finish coat. Some specific surfaces require specialized treatment. Vinyl Siding: Repaint vinyl siding with a color similar to the original color to avoid excess heat absorption and to prevent buckling or warping. Concrete, Stucco, Masonry, Block, Cement Composition Siding: All new surfaces must be cured. Remove all form release and curing agents. If the pH is higher than 8, prime with a masonry primer. Rough surfaces may be smoothed with block filler. Cracks, voids and other holes should be repaired with an elastomeric patch or sealant. For drastic color changes or deep, vivid colors, prime with this product or an appropriate tintable primer for your optimal color accuracy and coverage.

### **LEAD WARNING**

WARNING! If you scrape, sand or remove old paint, you may release lead dust. LEAD IS TOXIC. EXPOSURE TO LEAD DUST CAN CAUSE SERIOUS ILLNESS, SUCH AS BRAIN DAMAGE, ESPECIALLY IN CHILDREN. PREGNANT WOMEN SHOULD ALSO AVOID EXPOSURE. Wear a NIOSH-approved respirator to control lead exposure. Clean up carefully with a HEPA vacuum and a wet mop. Before you start, find out how to protect yourself and your family by contacting the National Lead Information Hotline at 1-800-424-LEAD or log on to [www.epa.gov/lead](http://www.epa.gov/lead).

### **LIFETIME LIMITED WARRANTY**

LIFETIME LIMITED WARRANTY: If this product, when applied according to product application instructions, to a properly prepared exterior residential surface, peels or blisters, for as long as you own your residence, Valspar shall, upon presentation of proof-of-purchase to the store where the product was purchased, either replace an equivalent quantity of product sufficient to repair the peeling or blistering free of charge or refund the original purchase price. This warranty shall not apply to any defect or damage resulting from improper surface preparation, structural defects, failure of a previous paint or improper application of the product. This is your sole remedy under this warranty. This warranty is made to the original residential consumer paint purchaser and is not transferable. THIS WARRANTY EXCLUDES (1) LABOR OR COSTS ASSOCIATED WITH LABOR FOR THE APPLICATION OR REMOVAL OF ANY PRODUCT, AND (2) ANY INDIRECT, SPECIAL, INCIDENTAL OR CONSEQUENTIAL DAMAGES. Some states do not allow the exclusion or limitation of incidental or consequential damages, so the above limitation or exclusion may not apply to you. This warranty gives you specific legal rights and you may also have other rights which vary from state to state. [Valsparpaint.com/1-877-VALSPAR](http://Valsparpaint.com/1-877-VALSPAR).

### **CAUTIONS**

Use only with adequate ventilation. To avoid overexposure, open windows and doors or use other means to ensure fresh air entry during application and drying. If you experience eye watering, headaches, or dizziness, increase fresh air, or wear respiratory protection (NIOSH approved) or leave the area. Adequate ventilation required when sanding or abrading the dried film. If adequate ventilation cannot be provided wear an approved particulate respirator (NIOSH approved). Follow respirator manufacturer's directions for respirator use. Avoid contact with eyes and skin. Wash hands after using. Keep container closed when not in use. Do not transfer contents to other containers for storage. FIRST AID: In case of eye contact, flush thoroughly with large amounts of water. Get medical attention if irritation persists. If swallowed, call Poison Control Center, hospital emergency room, or physician immediately. DELAYED EFFECTS FROM LONG TERM OVEREXPOSURE. Abrading or sanding of the dry film may release crystalline silica which has been shown to cause lung damage and cancer under long term exposure. WARNING: This product contains chemicals known to the State of California to cause cancer and birth defects or other reproductive harm. DO NOT TAKE INTERNALLY. KEEP OUT OF THE REACH OF CHILDREN.

**EMERGENCY MEDICAL TELEPHONE: 1-888-345-5732**

Valspar, Cleveland, Ohio 44115  
1-877-VALSPAR (825-7727)  
[valsparpaint.com](http://valsparpaint.com)  
Revised: 9/21/22  
Version: 2600SG