



**SUREGRIP®  
SEAM & REPAIR ADHESIVE**

**DESCRIPTION AND USES**

Rust-Oleum® SureGrip® Seam & Repair Adhesive is a seam adhesive designed to seal down stubborn, curling, loose edges, seams, tears and overlaps. It bonds strong and tacks fast, yet strips easily without damaging walls.

SureGrip Sea & Repair Adhesive is not intended for use where oil or grease is present or over silicone, wax-coated surfaces or non-stick surfaces treated with Teflon®, Tedlar® and similar non-stick coatings.

**PERFORMANCE CHARACTERISTICS**

- Seals sown loose seams, stubborn curling edges, tears and overlaps
- Grips in 10 seconds
- Dries clear, non-staining
- Easy water cleanup

**PRODUCTS**

SKU	Container Size
02861	2-ounce tube

**PRODUCT APPLICATION**

**APPLICATION**

Use only when temperature is between 50-100°F (10-38°C). Adhesive is ready to use. Apply a thin coat under edges. Make sure the adhesive gets back into areas where the wallcovering starts to separate from the surface. For separated seams, dampen the front and back of loose wallcovering or border with a damp sponge. Wait 5 minutes before applying adhesive. Smooth until flat. If the edges are curled, press down and hold for 10 seconds. Avoid contact with the surface of embossed or delicate wallcovering.

**PRODUCT APPLICATION (cont.)**

**DRY TIME**

Drying time will vary depending on the wallcovering type, temperature, ventilation and humidity in the room.

**CLEAN-UP**

Remove excess adhesive on or around the wallcovering or border immediately with a clean damp sponge or cloth. Blot dry with a soft towel. Additional effort may be required if adhesive is allowed to contact the surface of embossed or textured vinyl. Close tube tightly after each use.

**TOOL CLEAN-UP**

Clean tools with warm water.

**STORAGE**

Protect from freezing. Always keep the container tightly closed and store in a cool dry place at temperatures between 40-100°F (4-38°C). Normal storage life is one year. The disposal of excess or left over product should conform to local laws regarding water-based products.

**TECHNICAL DATA****SUREGRIP® SEAM & REPAIR ADHESIVE****PHYSICAL PROPERTIES**

	SUREGRIP SEAM & REPAIR ADHESIVE
Resin Type	Synthetic-based Seam Adhesive
Solvents	Water
Appearance	Clear
Odor	None
Volatile Organic Compounds (when mixed with water)	0 g/l
Practical Coverage at Recommended DFT (assumes 15% material loss)	Varies depending on porosity and application method.
Dry Times at 70-80°F (21-27°C) and 50% Relative Humidity	Drying time will vary depending on the wallcovering type, temperature, ventilation and humidity in the room.
Shelf Life	1 year
Flammability	Non-flammable
Safety	For additional information, see SDS

The technical data and suggestions for use contained herein are correct to the best of our knowledge, and offered in good faith. The statements of this literature do not constitute a warranty, express, or implied, as to the performance of these products. As conditions and use of our materials are beyond our control, we can guarantee these products only to conform to our standards of quality, and our liability, if any, will be limited to replacement of defective materials. All technical information is subject to change without notice.